



the LED lighting source™  
 COMMERCIAL • LANDSCAPE • ARCHITECTURAL • RESIDENTIAL

15 Brownridge Rd. Unit 6, Halton Hills, ON L7G 0C6 • 905-487-8192 • 1-877-LED-2DAY • SGIlighting.com

Project: \_\_\_\_\_

Client: \_\_\_\_\_

Part #: UND-P-1W-CYL-12VAC-BRS - 45 - lc

Date:    /    /    Qty: \_\_\_\_\_

SPECIFICATION

## LED Underwater Light • 1 Watt Cylinder



<b>Operating Voltage (ov)</b>	12V AC		
<b>Finish (fin)</b>	BRS	Brass	
<b>Beam Angle (ba)</b> Degrees	45°		
<b>Light Colour (lc)</b> Correlated Colour Temperature (CCT)	2700K	Incandescent White	
	3000K	Warm White	
	4000K	Neutral White	
	5000K	Cool White	
	Specify Kelvin (K) for other CCTs*		
	R Red* G Green* B Blue* A Amber*		
<b>Light Output</b> Lumens	3000K	99	
	4000K	108	
	5000K	119	
<b>IP Rating</b>	IP68		
<b>Dimension</b> Diameter, Height	D	1.14"	29 mm
	H	2.16"	55 mm
<b>Housing</b>	Brass		
<b>Watts</b>	1W		
<b>Light Source</b>	1 x 1W LED		
<b>Input Voltage</b>	AC 100V – 240V, 277V external transformer		
<b>Dimmable</b>	Yes – with dimmable transformer		
<b>Operating Temperature</b>	-25°C to +50°C		-13°F to 122°F
<b>Life</b> Lumen Maintenance	50,000 hours		

### Part Number Configuration – UND-P-1W-CYL-ov-fin-ba-lc

Category	Grade	Family	Operating Voltage (ov)	Finish (fin)	Beam Angle (ba)	Light Colour (lc)
UND	P-Professional	1W CYL	12VAC	BRS Brass	45°	<b>2700K</b> IW <b>3000K</b> WW <b>4000K</b> NW <b>5000K</b> CW <b>R*</b> G* <b>B*</b> A*

\* Available on special order