



the LED lighting source™

COMMERCIAL • LANDSCAPE • ARCHITECTURAL • RESIDENTIAL

15 Brownridge Rd. Unit 6, Halton Hills, ON L7G 0C6 • 905-487-8192 • 1-877-LED-2DAY • SGIlighting.com

Project: _____

Client: _____

Part #: UND-P-18W-FNT-24VDC-SIL-ba-lc

Date: / / Qty: _____

SPECIFICATION

LED Underwater Light • 18 Watt Fountain



Operating Voltage (ov)	24V DC Constant Voltage		
Finish (fin)	SIL	Silver	
Beam Angle (ba) Degrees	15°	60°*	45° RGB only*
Light Colour (lc) Correlated Colour Temperature (CCT)	2700K	Incandescent White	
	3000K	Warm White	
	4000K	Neutral White	
	5000K	Cool White	
	RGB	Colour Changing*	
	Specify Kelvin (K) for other CCTs*		
	R Red*	G Green*	B Blue* A Amber*
Light Output Lumens	3000K	1330	
	4000K	1572	
	5000K	1764	
IP Rating	IP68		
Dimension Diameter, Height	D	7.78"	200 mm
	H	1.97"	50 mm
Housing	Stainless Steel		
Watts	18W		
Light Source	18 x 1W LED		
Input Voltage	AC 100V – 240V, 277V external transformer		
Dimmable	Yes – with dimmable transformer		
Operating Temperature	-25°C to +50°C		-13°F to 122°F
Life Lumen Maintenance	50,000 hours		

Part Number Configuration – UND-P-18W-FNT-ov-fin-ba-lc

Category	Grade	Family	Operating Voltage (ov)	Finish (fin)	Beam Angle (ba)	Light Colour (lc)
UND	P-Professional	18W FNT	24VDC	SIL Silver	15° 45° 60°*	2700K IW 3000K WW 4000K NW 5000K CW RGB R* G* B* A*

* Available on special order