



the LED lighting source™

COMMERCIAL • LANDSCAPE • ARCHITECTURAL • RESIDENTIAL

15 Brownridge Rd. Unit 6, Halton Hills, ON L7G 0C6 • 905-487-8192 • 1-877-LED-2DAY • SGIlighting.com

Project: \_\_\_\_\_

Client: \_\_\_\_\_

Part #: BUL - P - 1W - REC - ov - SIL - ba - lc

Date:      /      /      Qty: \_\_\_\_\_

SPECIFICATION

## LED Bullet Light • 1 Watt Recessed



<b>Operating Voltage (ov)</b>	12V DC 350 mA	Constant Voltage Constant Current*
<b>Finish (fin)</b>	SIL	Silver
<b>Beam Angle (ba)</b> Degrees	60°	15°*    38°*
<b>Light Colour (lc)</b> Correlated Colour Temperature (CCT)	2700K 3000K 4000K 5000K	Incandescent White Warm White Neutral White Cool White Specify Kelvin (K) for other CCTs* R Red*    G Green*    B Blue*    A Amber*
<b>Light Output</b> Lumens	3000K 4000K 5000K	67.9 80.5 93.1
<b>IP Rating</b>	IP55	IP65*
<b>Dimension</b> Diameter, Fixture Height (full height), Trim Height, Hole Size	D FH TH HS	1.65"    42 mm 1"        25 mm 0.11"    3 mm 1.37"    35 mm
<b>Housing</b>	Aluminum Finish	
<b>Watts</b>	1W	
<b>Light Source</b>	1 x 1W LED	
<b>Input Voltage</b>	AC 100V – 240V, 277V	external driver
<b>Dimmable</b>	Yes	With dimmable driver
<b>Operating Temperature</b>	-25°C to +50°C	-13°F to 122°F
<b>Life</b> Lumen Maintenance	50,000 hours	

### Part Number Configuration – BUL-P-1W-REC-ov-fin-ba-lc

Category	Grade	Family	Operating Voltage (ov)	Finish (fin)	Beam Angle (ba)	Light Colour (lc)
BUL	P- Professional	1W REC	12VDC 350MA *	SIL Silver	15°* 38°* 60°	2700K IW 3000K WW 4000K NW 5000K CW R* G* B* A*

\* Available on special order