



the LED lighting source™

COMMERCIAL • LANDSCAPE • ARCHITECTURAL • RESIDENTIAL

15 Brownridge Rd. Unit 6, Halton Hills, ON L7G 0C6 • 905-487-8192 • 1-877-LED-2DAY • SGIlighting.com

Project: _____

Client: _____

Part #: DECK – P – 1W – SQR – 12VDC – SST – 120 – lc

Date: / / Qty: _____

SPECIFICATION

LED Deck Light • 0.5 Watt Square



Operating Voltage (ov)	12V DC	Constant Voltage	
Finish (fin)	SST	Stainless Steel	
Beam Angle (ba) Degrees	120°		
Light Colour (lc) Correlated Colour Temperature (CCT)	2700K	Incandescent White	
	3000K	Warm White	
	4000K	Neutral White	
	5000K	Cool White	
	RGB	Colour Changing	
	Specify Kelvin (K) for other CCTs*		
	R Red*	G Green*	B Blue* A Amber*
Light Output Lumens	3000K	34	
	4000K	36.5	
	5000K	39	
IP Rating	IP65		
Dimension Width/Length, Height Hole Width/Length	W/L	2.2"	56 mm
	H	1.1"	28 mm
	HWL	2"	50 mm
Housing	Stainless Steel & Tempered Glass		
Watts	0.5W		
Light Source	1 x 0.5W LED		
Input Voltage	AC 100V – 240V, 277V external transformer		
Dimmable	Yes With dimmable transformer		
Operating Temperature	-25°C to +50°C		-13°F to 122°F
Life Lumen Maintenance	50,000 hours		

Part Number Configuration – DECK-P-1W-SQR-ov-fin-ba-lc

Category	Grade	Family	Operating Voltage (ov)	Finish (fin)	Beam Angle (ba)	Light Colour (lc)
DECK	P-Professional	1W SQR	12VDC	SST Stainless Steel	120°	2700K IW 3000K WW 4000K NW 5000K CW RGB R* G* B* A*

* Available on special order