



the LED lighting source™

COMMERCIAL • LANDSCAPE • ARCHITECTURAL • RESIDENTIAL

15 Brownridge Rd. Unit 6, Halton Hills, ON L7G 0C6 • 905-487-8192 • 1-877-LED-2DAY • SGIlighting.com

Project: _____

Client: _____

Part #: ING - P - 1W - MCYL - 12VDC - SST - 120 - lc

Date: / / Qty: _____

SPECIFICATION

LED Inground Light • 0.6 Watt Mini Cylinder



Operating Voltage (ov)	12V DC	Constant Voltage
Finish (fin)	SST	Stainless Steel
Beam Angle (ba) Degrees	120°	
Light Colour (lc) Correlated Colour Temperature (CCT)	2700K Incandescent White 3000K Warm White 4000K Neutral White 5000K Cool White RGB Colour Changing Specify Kelvin (K) for other CCTs* R Red* G Green* B Blue* A Amber*	
Light Output Lumens	3000K	21
	4000K	22.5
	5000K	24
IP Rating	IP67	
Dimension Diameter, Fixture Height (full height), Trim Height, Hole Size	D	1.10" 28 mm
	FH	1.06" 27 mm
	TH	0.11" 3mm
	HS	0.78" 20 mm
Housing	Stainless Steel	
Watts	0.6W	
Light Source	1 x 0.6W LED	
Input Voltage	AC 100V – 240V, 277V	external transformer
Dimmable	Yes	With dimmable transformer
Operating Temperature	-25°C to +50°C	-13°F to 122°F
Life Lumen Maintenance	50,000 hours	

Part Number Configuration – ING-P-1W-MCyl-ov-fin-ba-lc

Category	Grade	Family	Operating Voltage (ov)	Finish (fin)	Beam Angle (ba)	Light Colour (lc)
ING	P-Professional	1W MCYL	12VDC	SST Stainless Steel	120°	2700K IW 3000K WW 4000K NW 5000K CW RGB R* G* B* A*

* Available on special order