



the LED lighting source™  
 COMMERCIAL • LANDSCAPE • ARCHITECTURAL • RESIDENTIAL

15 Brownridge Rd. Unit 6, Halton Hills, ON L7G 0C6 • 905-487-8192 • 1-877-LED-2DAY • SGiLighting.com

Project: \_\_\_\_\_

Client: \_\_\_\_\_

Part #: ING - P - 1W - CYL - 12VAC - BNZ - 45 - lc

Date:      /      /      Qty: \_\_\_\_\_

SPECIFICATION

## LED Inground Light • 1 Watt Cylinder



<b>Operating Voltage (ov)</b>	12V AC	Constant Current
<b>Finish (fin)</b>	BNZ	Architectural Bronze
<b>Beam Angle (ba)</b> Degrees	45°	
<b>Light Colour (lc)</b> Correlated Colour Temperature (CCT)	2700K Incandescent White 3000K Warm White 4000K Neutral White 5000K Cool White RGB Colour Changing Specify Kelvin (K) for other CCTs* R Red* G Green* B Blue* A Amber*	
<b>Light Output</b> Lumens	3000K	45
	4000K	49.5
	5000K	54
<b>IP Rating</b>	IP68	
<b>Dimension</b> Diameter, Fixture Height (full height), Trim Height, Hole Size	D	1.5" 38 mm
	FH	1.7" 43 mm
	TH	0.11" 3 mm
	HS	1.18" 30 mm
<b>Housing</b>	Aluminum Alloy	
<b>Watts</b>	1W	
<b>Light Source</b>	1 x 1W LED	
<b>Input Voltage</b>	AC 100V – 240V, 277V external transformer	
<b>Dimmable</b>	Yes With dimmable transformer	
<b>Operating Temperature</b>	-25°C to +50°C -13°F to 122°F	
<b>Life</b> Lumen Maintenance	50,000 hours	

### Part Number Configuration – ING-P-1W-CYL-ov-fin-ba-lc

Category	Grade	Family	Operating Voltage (ov)	Finish (fin)	Beam Angle (ba)	Light Colour (lc)
ING	P-Professional	1W CYL	12VAC	BNZ Architectural Bronze	45°	<b>2700K</b> IW <b>3000K</b> WW <b>4000K</b> NW <b>5000K</b> CW <b>RGB</b> <b>R*</b> G* <b>B*</b> A*

\* Available on special order