



the LED lighting source™

COMMERCIAL • LANDSCAPE • ARCHITECTURAL • RESIDENTIAL

15 Brownridge Rd. Unit 6, Halton Hills, ON L7G 0C6 • 905-487-8192 • 1-877-LED-2DAY • SGiLighting.com

Project: \_\_\_\_\_

Client: \_\_\_\_\_

Part #: PUCK – P – 3W – MINI – 12VDC – BLK – ba – lc

Date:      /      /      Qty: \_\_\_\_\_

SPECIFICATION

## LED Puck Light • 3 Watt Mini UnderMount



<b>Operating Voltage (ov)</b>	12V DC	Constant Voltage	
<b>Finish (fin)</b>	BLK	Black	
<b>Beam Angle (ba)</b> Degrees	38°	15°*	60°*
<b>Light Colour (lc)</b> Correlated Colour Temperature (CCT)	2700K	Incandescent White	
	3000K	Warm White	
	4000K	Neutral White	
	5000K	Cool White	
	Specify Kelvin (K) for other CCTs*		
	R Red*	G Green*	B Blue* A Amber*
<b>Light Output</b> Lumens	3000K	185	
	4000K	193.5	
	5000K	202	
<b>IP Rating</b>	IP55	IP65*	
<b>Dimension</b> Diameter, Height	D	1.65"	42 mm
	H	1"	25 mm
<b>Housing</b>	Aluminum Alloy		
<b>Watts</b>	3W		
<b>Light Source</b>	3 x 1W LED		
<b>Input Voltage</b>	AC 100V – 240V, 277V external transformer		
<b>Dimmable</b>	Yes	With dimmable transformer	
<b>Operating Temperature</b>	–25°C to +50°C		–13°F to 122°F
<b>Life</b> Lumen Maintenance	50,000 hours		

### Part Number Configuration – PUCK-P-3W-MINI-ov-fin-ba-lc

Category	Grade	Family	Operating Voltage (ov)	Finish (fin)	Beam Angle (ba)	Light Colour (lc)
PUCK	P-Professional	3W MINI	12V DC	BLK Black	15°* 38° 60°*	2700K IW 3000K WW 4000K NW 5000K CW R* G* B* A*

\* Available on special order