



the LED lighting source™

COMMERCIAL • LANDSCAPE • ARCHITECTURAL • RESIDENTIAL

15 Brownridge Rd. Unit 6, Halton Hills, ON L7G 0C6 • 905-487-8192 • 1-877-LED-2DAY • SGiLighting.com

Project: _____

Client: _____

Part #: DOWN-12WS-350MA- WHT - 60 - lc

Date: / / Qty: _____

SPECIFICATION

LED Downlight • 12 Watt Swivel Standard



Operating Voltage (ov)	350 mA 16 V DC 19.5 V DC	Constant Current Typical Maximum
Finish (fin)	WHT	White
Beam Angle (ba) Degrees	60°	
Light Colour (lc) Correlated Colour Temperature (CCT)	3000K 5000K	Warm White Cool White
Light Output Lumens	3000K 5000K	765 841
IP Rating	IP55	
Dimension Diameter, Height, Hole Size	D H HS	5.31" 2.32" 5" 135 mm 59 mm 127 mm
Housing	Aluminum Alloy	
Watts	12W	
Light Source	12 x 1W LED MLT Multiple LED Source	
Input Voltage	AC 100V – 240V, 277V external driver	
Dimmable	Yes – with dimmable driver	
Operating Temperature	-25°C to +50°C -13°F to 122°F	
Life Lumen Maintenance	50,000 hours	

Standard Grade

Part Number Configuration – DOWN-12WS-ov-fin-ba-lc

Category	Family	Operating Voltage (ov)	Finish (fin)	Beam Angle (ba)	Light Colour (lc)
DOWN S	12WS	350MA	WHT White	60°	3000K WW 5000K CW