



the LED lighting source™  
 COMMERCIAL • LANDSCAPE • ARCHITECTURAL • RESIDENTIAL

15 Brownridge Rd. Unit 6, Halton Hills, ON L7G 0C6 • 905-487-8192 • 1-877-LED-2DAY • SGIlighting.com

Project: \_\_\_\_\_

Client: \_\_\_\_\_

Part #: DOWN-14WS-350MA- fin - ba - lc

Date:    /    /    Qty: \_\_\_\_\_

SPECIFICATION

## LED Downlight • 14 Watt Swivel



<b>Operating Voltage (ov)</b>	350 mA 18 V DC 40 V DC	Constant Current Typical Maximum
<b>Finish (fin)</b>	WHT SIL	White Silver BLK Black*
<b>Beam Angle (ba)</b> Degrees	60°	30°* 42°*
<b>Light Colour (lc)</b> Correlated Colour Temperature (CCT)	2700K 3000K 3500K 4000K 5000K	Incandescent White Warm White Sand White Neutral White Cool White Specify Kelvin (K) for other CCTs*
<b>Light Output</b> Lumens	3000K 3500K 4000K 5000K	1056 1082 1108 1164
<b>IP Rating</b>	IP55	
<b>Dimension</b> Diameter, Height, Hole Size	D H HS	3.34" 3.34" 3" 85 mm 85 mm 75 mm
<b>Housing</b>	Aluminum Alloy	
<b>Watts</b>	14W	
<b>Light Source</b>	1 x 14W LED COB Chip on Board	
<b>Input Voltage</b>	AC 100V – 240V, 277V external driver	
<b>Dimmable</b>	Yes – with dimmable driver	
<b>Operating Temperature</b>	-25°C to +50°C -13°F to 122°F	
<b>Life</b> Lumen Maintenance	50,000 hours	

### Part Number Configuration – DOWN-14WS-ov-fin-ba-lc-hou

Category	Family	Operating Voltage (ov)	Finish (fin)	Beam Angle (ba)	Light Colour (lc)	Housing (hou)
DOWN	14WS	350MA	WHT White BLK Black* SIL Silver*	30°* 42°* 60°	2700K IW 3000K WW 3500K SW 4000K NW 5000K CW	3NC 3" New Construction (IC rated) N None

\* Available on special order