LED Flex LightUltraBright 4.4 Watt RGB IP68



High Output - UltraBright 4.4 Watt RGB IP68









LED Flex Light • UltraBright 4.4 Watt RGB IP68

IP Rating

Dimension

Beam Angle (ba) Degrees



Length	Custom Length ² cuttable every 4.0"(101.6 mm)			
Operating Voltage	24V DC			
Finish (fin)	WHTC Clear White WHTF Frosted White ¹ BLKC Clear Black ¹			
Light Colour (Ic)	RGB Colour Changing			
Correlated Colour Temperature (CCT)	Also available in Whites and Single Colours Please see individual product spec sheets			




Light Output	RGB White	336.6	per foot
Lumens	KGD WITHE	556.6	per roor

120°

IP68¹ W

0.551"

14 mm



Width, Height, Length

L

Specify maximum length in inches

Watts 4.4 Watts per foot

Input Voltage AC 100V – 240V, 277V external transformer

Yes With dimmable transformer

MLV, ELV, Phase or 0-10V.

Please specify at time of order. Sold separately.

Operating Temperature -25°C to +50°C -13°F to 122°F

Life Lumen Maintenance 50,000 hours

5 Years

Dimensions in millimeters

Recommended Tracks	LP2410	REC2421	UCH2428	GENIE_PROFILE-DOME
--------------------	--------	---------	---------	--------------------

See track page for more compatible tracks. See individual track cutsheets for more details.

Warranty

Part Number Configuration

FLEX	ULTRA_4.4W-IP68	24VDC		RGB
Category	Family (fam)	Operating Voltage (ov)	Finish (fin)	Light Colour (Ic)
FLEX	ULTRA_4.4W-IP68 ¹	24V DC	WHTC Clear White WHTF Frosted White ¹ BLKC Clear Black ¹	RGB




Project Type








LED Flex Light • UltraBright 4.4 Watt RGB IP68 • Track Options

Please visit our products page on our website to view all tracks, along with track specifications.












Project Type






LED Flex Light • UltraBright 4.4 Watt RGB IP68 • Wiring



LED FLEX - WIRING CONFIGURATION EXAMPLES

The following illustrations are guides only. They are here to introduce general wiring configurations. See wattage chart below for more information on maximum run lengths.

HOMERUN mulitiple light strips back to the power supply. Maximum light length is 32 feet on Class 1 transformers.



CUSTOMIZE with small jumpers to incorporate unique lengths into run. Homerun back to power supply after 32 ft (Class 1 only).



FLEX-ULTRA_4.4W-IP68-24VDC-fin-RGB - POWER-21-24VDC-watt DIMMABLE (12VDC Power options available)

Power Supply	20 Watt class 2	40 Watt class 2	60 Watt class 2	96 Watt class 2	150 Watt class 1	200 Watt class 1	300 Watt class 1
¹Max ft of light	3 ft	7 ft	10 ft	17 ft	27 ft	36 ft*	54 ft*
Max cable distance between	12 AWG > 300 ft 14 AWG 238 ft	12AWG 189ft 14AWG 119ft	12AWG 126ft 14AWG 79ft	12 AWG 68ft 14 AWG 43ft	12 AWG 46ft 14 AWG 29ft	12 AWG 35ft 14 AWG 21ft	12 AWG 23ft 14 AWG 14ft
power & light	16 AWG 149ft 18 AWG 94ft	16 AWG 74ft 18 AWG 47ft	16AWG 49ft 18AWG 31ft	16 AWG 27ft 18 AWG 17ft	16AWG 18ft 18AWG 11ft	16AWG 13ft 18AWG 9ft	16AWG 9ft 18AWG 6ft

^{*} Every 32 linear feet of light must be home-run to transformer. **All installations in North America must follow Class 2 requirements. 1At 80% capacity




Project Type








LED Flex Light • UltraBright 4.4 Watt RGB IP68 • Cable Options

Cable Options for Colour Changing – Choose between Quick Connect or Hardwire option
Choose between 2 Ft, 5 Ft or 10 Ft cable leads











LED Flex LightUltraBright 4.4 Watt RGB IP68

SGi's UltraBright 4.4 Watt RGB IP68 is a versatile choice for unconventional and exciting lighting installations. UltraBright 4.4 Watt RGB IP68's small and compact size allows it to be hidden from view, perfect for unobtrusive underwater applications. Engineered to provide the highest possible quality available, UltraBright 4.4 Watt RGB IP68 is a great option for distinct and creative lighting designs. Available in a dazzling multi-colour colour changing RGB. Pair with LED Track to achieve a directional or diffused lighting effect.







